

T2150 Dot Matrix Printer

Fast, reliable class leading printers



Tally

SPEED ENHANCEMENT

- Print speeds up to **900 cps**
- 26,000 pages per month workload
- 80 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional
- Graphics Speed Performance increases more than 30%

The T2150 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure that it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the T2150S features a cutting device which separates forms automatically.

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Available Configuration:

- T2150** Standard Product
- T2150S** With Automatic Cutter
- LA550N** DEC compatible version

Print Speed	>900cps 15cpi, >720cps 12cpi, >600cps 10cpi
Resolution	Up to 360 x 360dpi
Printhead Life	400 million characters
Memory	128Kb
Standard Connectivity	Parallel (bi-directional) and serial RS232
Optional Connectivity	Serial current loop (20mA), Ethernet 10/100 Base T, USB Parallel Adapter, HostCom pocket coax matrix for IBM mainframe HostCom pocket twinax for AS400, iSeries, System 3X
Standard Emulation	IBM proprinter XL24, Epson LQ2550, Tally MTPL + barcode + LCP
Optional Emulation	DEC LA75; MT50 (Diskette and manual program packs)
Fonts	HS draft (sans serif), draft (sans serif), Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 barcodes and large character printing. Range of Arabic fonts (Arabic model)
Consumables	Ribbon: 5.0 million characters
STD Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA). Cut sheet front insertion with AGA
Opt'l Paper Handling	Additional push tractor, Front; Additional push tractor, Rear; Front single-bin automatic sheet feeder. Paper cutting device (T2150S only).
Paper Type	Continuous forms, Cut sheet
Paper Weight	Continuous forms 60-120gsm; Cut sheet 80-120gsm
Paper Size	Cut-sheet & Continuous forms: 76 - 278mm wide; Cut-sheet: 76-305mm long, Continuous forms: 76-559mm long
No. of Copies	Original 1 + 5 ply
Physical Weight	9Kg
PhysicalSize	(HxWxD): 300x460x295mm
Power Voltage	230V
Power Consumption	40W printing
Workload	26,000 pages per month
Drivers	Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	53dB(A)
Warranty	1 year on-site



ООО «Компания ИНФОСЭЛ»

Москва, ул. Ибрагимова, д. 31, оф. 401
Бизнес центр «Семеновский»

infocellprint.ru +7 (495) 651-82-85

All company and product names are trademarks or registered trademarks of their respective owner.
Specifications are subject to change without notice.

Copyright © 2010 DASCOM AP Pte Ltd

Ver. 1.0
Printed Date: 16/08/2010

DASCOM

DASCOM AP Pte Ltd
63 Hillview Avenue #08-22
Lam Soon Industrial Building
Singapore 669569
Tel: +65 6760 8833
Fax: +65 6760 1066
www.dascom.com.sg