

2280+ Dot Matrix Printer

High speed, rugged design for heavy duty operation



Tally

- Print speeds up to 1000 cps
- Full range of automatic features minimising operator intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard. Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS optional
- Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems

The 2265+ and 2280+ are undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just 'sprinters'; reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems.

The 2265+ and 2280+ printers are the first high speed matrix printers to incorporate Ethernet on-board.

Available Configuration:

2280+
2280+ 2T with two additional tractors
LA800+ DEC compatible version

Print Speed	Draft: 800cps; NLQ: 222cps; LQ: 111cps
Resolution	Up to 360 x 360 dpi
Throughput	(ECMA 132 @ 10cpi) Letter Performance: 626 pages per hour; Spreadsheet: 389 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 M Characters
Printhead Type	24 wire
Standard Connectivity	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
Optional Connectivity	Serial RS232, adapters, Ethernet IPDS: USB parallel adapter
Standard Emulation	MTPL + barcode/LCP, Epson LQ (Esc P/2), IBM ProPrinter XL24e
Optional Emulation	MT50, MT460, Digital/Compaq model (LA800) contextual Arabic
Fonts	Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 Barcodes and scaleable LCP Font. Range of Arabic fonts (Arabic mode)
Consumables	Black Ribbon: 20 million characters
STD Paper Handling	Push tractors with paper parking and AGA; 2nd rear push tractor - 2280-2T only, 1+1 copies; Cut sheet front insertion with AGA
Opt'l Paper Handling	2nd front tractor (user installable); Dual bin automatic sheet feeder*, 190 sheets per bin; Face down output bin*; Paper cutting device, paper pedestal; Front feed sheet feeder, 190 sheets capacity
Number of Copies	1+5 copies. (1+1 for rear tractors of 2280-2T)
Paper Type	Continuous forms; Cut sheet
Paper Weight	Continuous forms: 60-120gsm; Cut sheet: 60-90gsm
Paper Size	Cut sheet: 100 to 420mm wide
Physical Weight	19Kg
Physical Size	(HxWxD): 277x623x430mm
Power Voltage	230V
Power Consumption	75W printing
Workload	Up to 50,000 pages per month
Reliability MTBF	10,000 hours
Drivers	Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP
Temperature	+10°C to +35°C
Humidity	20% to 80%
Acoustic	57dB(A)
Warranty	1 year on-site
Note	*The dual bin sheet feeder and face down output bin are unsuitable for use with the 2280-2T. Exceeding the monthly duty cycle will not void the warranty if DASCOS consumables and maintenance kits are used



ООО «Компания ИНФОСЭЛ»

Москва, ул. Ибрагимова, д. 31, оф. 401
Бизнес центр «Семеновский»

infocellprint.ru +7 (495) 651-82-85

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOS AP Pte Ltd

Ver. 1.0
Printed Date: 03/07/2009

DASCOS

DASCOS AP Pte Ltd
63 Hillview Avenue #08-22
Lam Soon Industrial Building
Singapore 669569
Tel: +65 6760 8833
Fax: +65 6760 1066
www.dascom.com.sg