Dascom

2365 MC Dot Matrix Printer

Powerful & Rugged for Heavy Duty Operation



- Up to 9-part forms
- Full range of automatic features to minimize user intervention
- Ideal for 'On Demand' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard
- Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems including Windows; UNIX; DOS; SAP; R3 and Legacy systems

The 2365 MC and 2380 printers are rugged and powerful high speed matrix printers for heavy duty operation under the most extreme conditions. Reliable, heavy workload output is guaranteed for many years following printer purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

Fully automated operation, coupled with the 'straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Features & Specifications

2365 MC Dot Matrix Printer

| Print Speed | At 10, 12 cpi: High Speed Draft 640, 800; Draft 533, 640; NLQ 180, 215 |
|------------------------------|---|
| Print Method | Serial Impact |
| Resolution | 360 x 360 dpi |
| Throughput | 587 pages per hour (ECMA 132) |
| Character Density | 5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent) |
| Line Density | 2, 3, 4, 6, 8, 12 lpi |
| Printhead Life | 500 M Characters (draft) |
| Printhead Type | 24 wire |
| Standard Connectivity | Bi-directional Parallel plus Ethernet 10/ 100BaseT with 128kb buffer |
| Optional Connectivity | RS232 Serial, Adapters, Twinax/Coax, Ethernet IPDS |
| Standard Emulation | IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP |
| Optional Emulation | PCL3 (rugged writer) |
| Fonts | HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP fonts. |
| Consumables | 20 M Character Ribbon |
| STD Paper Handling | Push tractor with paper parking and AGA |
| Opt'l Paper Handling | 2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device |
| Number of Copies | Original + 8 (9-part forms) |
| Paper Type | Continuous forms |
| Paper Weight | 60-120gsm |
| Paper Size | 100 to 420mm wide |
| Physical Weight | 19Kg |
| PhysicalSize | (HxWxD): 280x623x432mm |
| Power Voltage | 120V/230V |
| Power Consumption | 60 Watts printing, Max 18 Watts in sleep mode |
| Compliance | Energy Star qualified, Ozone-free. RoHS, Microsoft, ISO-compliant |
| Workload | Up to 48,000 pages per month |
| Reliability MTBF | 12,500 hours @ 25% duty cycle |
| Drivers | Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP |
| Temperature | +10°C to +35°C |
| Humidity | 20% to 80% |
| Acoustic | 59dBA (ISO 7779) |
| Warranty | 1 year on-site |
| - | 2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device |
| Note | For OCR applications it is recommended that your readers are tested with print samples supplied by TallyGenicom prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions. |



All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM AP Pte Ltd

Ver. 1.0 Printed Date: 03/07/2009

DASCOM

DASCOM AP Pte Ltd 63 Hillview Avenue #08-22 Lam Soon Industrial Building Singapore 669569 Tel: +65 6760 8833 Fax: +65 6760 1066 www.dascom.com.sg